

**WEJ431** Adjustable Accurate Reference Source**FEATURES**

- The output voltage can be adjusted to 36V  
 Low dynamic output impedance, its typical value is  $0.2\Omega$   
 Trapping current capability is 1 to 100mA  
 The typical value of the equivalent temperature factor in the whole temperature scope is  $50 \text{ ppm}/^\circ\text{C}$   
 The effective temperature compensation in the working range of full temperature  
 Low output noise voltage  
 Fast on -state response


**SOT-23-3L**

1. REFERENCE



2. CATHODE

3. ANODE

**ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)**

Parameter	Symbol	Value	Units
Cathode Voltage	$V_{KA}$	37	V
Cathode Current Range (Continuous)	$I_{KA}$	-100--+150	mA
Reference Input Current Range	$I_{ref}$	0.05--+10	mA
Power Dissipation	$P_D$	770	mW
Operating temperature	$T_{opr}$	0-70	°C
Storage temperature Range	$T_{stg}$	-65--+150	°C

**ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)**

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Reference Input Voltage	$V_{ref}$	$V_{KA}=V_{REF}, I_{KA}=10\text{mA}$	2.450	2.5	2.550	V
Deviation of reference input Voltage Over temperature (note)	$\Delta V_{ref}/\Delta T$	$V_{KA}=V_{REF}, I_{KA}=10\text{mA}$ $T_{min} \leq T_a \leq T_{max}$		4.5	17	mV
Ratio Of Change in Reference Input Voltage to the change in Cathode Voltage	$\Delta V_{ref}/\Delta V_{KA}$	$I_{KA}=10\text{mA}$	$\Delta V_{KA}$ $=10\text{V}-V_{REF}$		-1.0	m V/V
			$\Delta V_{KA}$ $=36\text{V}-10\text{V}$		-0.5	m V/V
Reference Input Current	$I_{ref}$	$I_{KA}= 10\text{mA}, R_1=10\text{K}\Omega$ $R_2=\infty$		1.5	4	$\mu\text{A}$
Deviation Of Reference Input Current Over Full Temperature Range	$\Delta I_{ref}/\Delta T$	$I_{KA}=10\text{mA}, R_1=10\text{K}\Omega$ $R_2=\infty$ $T_A=\text{full Temperature}$		0.4	1.2	$\mu\text{A}$
Minimum cathode current for regulation	$I_{KA}(\min)$	$V_{KA}=V_{REF}$		0.45	1.0	mA
Off-state cathode Current	$I_{KA}(\text{OFF})$	$V_{KA}=36\text{V}, V_{REF}=0$		0.05	1.0	$\mu\text{A}$
Dynamic Impedance	$Z_{KA}$	$V_{KA}=V_{REF}, I_{KA}=1 \text{ to } 100\text{mA}$ $f \leq 1.0\text{KHz}$		0.15	0.5	$\Omega$

Note:  $T_{min}=0^\circ\text{C}$ ,  $T_{max}=+70^\circ\text{C}$ **CLASSIFICATION OF  $V_{ref}$** 

Rank	WEJ431	WEJ431 A	WEJ431 B
Range	2.487-2.512	2.475-2.525	2.450-2.550